

Grille Installation Instruction

Rev. 190401

Part#	G	R01F A/	IEC66 H	Applio	cation		02-2006 Cadillac Escalade /2002-2006 Cadillac le EXT /2002-2006 Cadillac Escalade ESV			
		Item	Part N	lame	QTY	Description	Item	Part Name	QTY	Description
Parts Lis		1	Billet Gr	ille	1	Aluminum	4	Truss Head Tapping Screws	10	10×3/4″
	ST	2	L Shape	Tabs	6		5	U-Clip Nuts	10	10#
		3	Kep Nut		1	1/4" -20	6	Hex Bolt	1	1/4" -20x3/4"
Install Notes: Overlay × Replacement √ Drill √ Cut √										
Step	Description illustration									
1	Id lis	-	the grille	& harc	lware \	with parts				130
2	Pry out plastic fasteners that attach filler panel to grille shell and core support. Save fasteners. Remove panel.									
3	Remove bolt near top front of grille shell, just right of center. Pull on upper ends of grille shell to release side mounting clips. Pull grill shell up and remove.									
4	Mask all painted areas of grille shell with masking tape. Lay grille shell on a soft surface. Carefully cut out center section of grille shell to within 1/8" of chrome. Cut out upper section of grille. Sand until within 1/32" of chrome. (See photo #1).									
5			le two U-clip nuts over each end of three "L" tabs. Loosely attach to lower mounting tabs of billet grille. e photo #2)							
6	Slide one U-clip nut on each end of billet grille upper side mounting tabs. Slide one U-clip nut on one end of two "L" tabs. Loosely attach to side mounting tabs. (See photo #3)									
7	ta	Center billet grille in rear of grille shell, and align top billet with upper edge of grille shell. Adjust lower mounting tabs to fit flush to bottom of grille shell. Adjust upper side mounting tabs to fit flush to underside of top of grille shell. Bend tabs as necessary to get proper fit. (See photo #4)								
8	М	Mark locations of mounting tab holes, and drill 1/4" holes into grille shell.								
9	Fa	asten a	ll screws	screws. Check alignment of billet grille. Make sure billet grille is flush to rear lip of grille shell						
10	br	acket t		"L" bracket to fastener in upper core support. Set grille shell back in vehicle. Attach long "L" bunting tab on grille shell with 1/4-20 hex head bolt and kep nut. Adjust grille shell out to clear lever.						

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Au	TO PARTS SPECIALIST INC.	Gril	le Installation Instruction	Rev. 190401
Part#	GR01HEC66 A/H	Application	For 2002-2006 Cadillac Escalad Escalade EXT /2002-2006 Cadil	
11	(Optional) Carefu	ılly pry Cadillac ε	emblem off factory grille. Reattach to upper o	center of billet grille.
	(Photo #1) To	op side cut d	etail (Photo #2) Note location	n of upper side mount
				26

12 Installation completed!!!

(Photo #3) Lower side mount

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

(Photo #4) Note location of upper crossbar