



# PATENT PRODUCT






## Grille Installation Instruction

Rev. 190901

|              |                    |                    |   |
|--------------|--------------------|--------------------|---|
| <b>Part#</b> | GR03FEI45<br>C/S/J | <i>Application</i> | For 2014-2020 Chevy Impala Logo Show (Not For 2014-2016 Chevy Impala Limited) |
|--------------|--------------------|--------------------|---|

|                   | Item | Part Name     | QTY | Description     | Item | Part Name | QTY | Description |
|-------------------|------|---------------|-----|-----------------|------|-----------|-----|-------------|
| <b>Parts List</b> | 1    | Billet Grille | 1   | Stainless steel | 3    | Bolt      | 4   | 6#-32x2"    |
|                   | 2    | Toggle Nut    | 4   | 6#-32           |      |           |     |             |

**Install Notes:** Overlay  Replacement  Drill  Cut

| Step | Description   | illustration  |
|------|---|---|
| 1    | Identify the grille & hardware with parts list.   |   |
| 2    | Optional: remove the plastic cover on the bottom of the OEM front bumper, which will allow access to the rear of the OEM grille.  |   |
| 3    | Before you install the new billet grille, please check if the OEM grille chrome pieces bar whether against new grille or not, if it does, remove those chrome bars before you install the new grille. |  <p style="color: red; font-size: small;">If the chrome pieces against grille, please remove those bars before you install.</p>  |
| 4    | Insert the screws into the weld tab hole from front side of the billet grille.  | <div style="border: 1px solid black; padding: 5px; display: inline-block;">Picture for reference only. This is not actual grille.</div>  <div style="display: flex; flex-direction: column; align-items: flex-end; margin-left: 10px;"> <div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Weld tab</div> <div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Screw</div> <div style="border: 1px solid black; padding: 2px;">Toggle nut</div> </div> |
| 5    | Center the billet grille onto the OEM grille. Press & insert the toggle nuts on to the rear of the OEM grille through the gap between the horizontal bars.  |   |
| 6    | Secure the grille using the toggle nuts and screws from the front side of the billet grille with a screw driver.  | <div style="border: 1px solid black; padding: 5px; display: inline-block; margin-bottom: 5px;">Bolts &amp; Toggle Nuts</div>    |
| 7    | Installation completed!!!   |   |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!