

7

Installation completed!!!

## **PATENT PRODUCT**

## Grille Installation Instruction

GR03FFC42C/J Application FOR 2015-2016 CHEVY CRUZE

Rev. 180601

| Pan#       |   | GRU3FFC42C/J  |            | Application |          |           | FOR 2015-2016 CHEVY CRUZE |              |              |  |           |             |          |           |      |             |  |
|------------|---|---|------------|-------------|----------|-----------|---------------------------|--------------|--------------|--|-----------|-------------|----------|-----------|------|-------------|--|
|            |   | Item  | Pa         | art Nam     | 9        | QTY       | D                         | esc          | ription      |  | Item      | Part        | Name     | QTY       |      | Description |  |
| Parts List |   | 1   | Billet Gr  | rille       |          | 2         | Stai                      | inless steel |              |  | 3         | Toggle Nuts |          | 8         | 6#-3 | 6#-32UNC    |  |
|            |   | 2 Stud  |            |             | 8        | 6#-3      |                           | 32UNCX2      |              |  |           |             |          |           |      |             |  |
| ınstall I  | Note  | es: Ov  | erlay      | $\sqrt{}$ F | Replac   | ement     | ×                         | <            | Drill        |  | $\sqrt{}$ | Cut         | $\times$ |           |      |             |  |
| Step       | Description   |   |            |             |          |           |                           |              | illustration |  |           |             |          |           |      |             |  |
| 1          | Optional (for vehicles with black plastic cover under hood). Pop hood, remove the black plastic cover (on top of OEM panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the panel of the grille shell. |   |            |             |          |           |                           |              |              |  |           |             |          |           |      |             |  |
| 3          | Cer   | shell and reattach after installation.  Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. You need mark an drill six holes. |            |             |          |           |                           |              |              |  |           |             |          |           |      |             |  |
| 4          | Sec   | Secure grille using the Toggle Nut from the back side of the OEM grille shell. Place screws through welded aluminum tabs on the grille.   |            |             |          |           |                           |              |              |  |           |             |          |           |      |             |  |
| 5          | Mal   | ke sure   | the grille | is centere  | d and ti | ghten the | faste                     | eners        |              |  |           |             |          |           |      |             |  |
| 6          | Rei   | nstall th   | ne black p | lastic cove | er which | was rem   | oved                      | l in st      | ep 2.        |  |           |             |          |           |      |             |  |
|            |   |   |            |             |          |           |                           |              |              |  |           |             |          | C 6 6 8 9 | 2    |             |  |

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!