



Part#	C66465C&J&S	Application	For 2006-2009 Chevy Trailblazer LT Not For LS/SS/2006-2008 Chevy Trailblazer LT 8Cyl Not For LS/SS
-------	-------------	-------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Stainless Steel	4	Machine Screws	4	6-32 × 2"
	2	Flange Brackets	4	2"	5	Nylon Lock Nuts	4	6-32
	3	Flat Washers	4	6#				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the grille shell from the vehicle; unfasten the seven mounting clips on the rear of the grille shell. Use a slotted screw driver to pry the clips.	
3	Place the lower insert in the lower opening of the factory grille. Hold the billet in place and insert a machine screw in both of the mounting brackets welded to the rear of the insert. Install a flange bracket (with the bent edges facing forward), washer and nylon lock nut on each machine screw from behind the factory grille shell. Now snug the two machine screws and nylon lock nuts (DO NOT OVER TIGHTEN) so the billet is held firmly in place.	
4	Repeat the installation of the upper insert as in Step 3.	
5	Reinstall the grille assembly which was removed in step 2.	
6	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!