

Grille Installation Instruction

Rev. 190501

Part# GR03FFD65V/E Application For 2006-2009 Chevy Trailblazer LT Not For LS/SS/2006-2008 Chevy Trailblazer LT 8Cyl Not For LS/SS

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Aluminum	3	Screws	10	6-32×1.5"
	2	Metal Brackets	10		4	K- Lock Nuts	10	6-32

Install Notes: Overlay Replacement Drill × Cut Step Description illustration Identify the grille & hardware with parts list. 1 Pop hood, remove plastic shroud at the top and set fasteners aside. 3 Optional: Using factory instruction, remove the entire front grille shell 4 Position the Billet Grille onto grille shell cavity. Loosely attach the grille by holding the Metal Brackets behind factory grille shell and inserting 5 the Phillips Screws(from the front) through the billet grille holes and metal brackets, secure them with flange nuts provided. 6 Once the billet grille are loosely attached, center them and tighten all phillips screws at the same rate. 7 Reinstall the black plastic cover which was removed in step 2. 8 Installation completed!!!

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!