	Grille Installation Instruction									Rev. 190501	
Part#						007-2010 Chevy Silverado 3500 HD /2007-2010 v Silverado 2500 HD					
		ltem	Part Nar	me QTY	Descri	ption	ltem	Part Name	QTY	Description	
Parts L	ist	1	Billet Grille	e 2	Stainless ste	el	3	Kep Nut	12	10-24	
		2 Slotted Studs		lds 12	10-24×2″		4	Flat Tab	12		
Install Notes: Overlay $\boxed{\sqrt{}}$ Replacement $\boxed{\times}$						< Dri		Cut	×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Secure the stud to the threaded holes on the rear of the grille.										
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
5	Secure grille using the flat tabs and kep nuts from the back side of the OEM grille shell.										
6	Make sure the grille is centered and tighten the fasteners.										
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!