




Grille Installation Instruction

Rev. 190401

Part#	GR04FEC75K		Application	For 2002-2008 Dodge Ram Regular Model Tow Hook Must Be Removed Not For Iaramie SLT 4X4/Sport Model/Daytona				
Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Studs	3	10-24×1 1/4"
	2	K-Lock Nuts	3	10-24	4	Washers	3	
Install Notes: Overlay <input checked="" type="checkbox"/> Replacement <input type="checkbox"/> Drill <input checked="" type="checkbox"/> Cut <input type="checkbox"/>								
Step	Description				illustration			
1	Identify the grille & hardware with parts list.							
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.							
3	Now thread studs into the grille. Then push the studs through the shell and center the grille into the opening. Mark and drill a 1/8" hole in each of the three locations. Fasten the grille use the washers and the k-lock nuts from the rear, but do not over-tighten.							
4	Make sure the grille is centered.							
5	Reinstall the black plastic cover which was removed in step 2.							
6	Installation completed!!!							

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!