

Grille Installation Instruction

Rev. 150116

Part# GR04FEG21H Application 94~01 Dodge RAM - 4-pc Billet Grille

		Item	Item Part Name		QTY Description		Item	Part Name		QTY	QTY Description	
Parts L	ist	1	Billet Grille		4	Aluminum	3	U- Clip Nu	ıts	8	8#	
		2	Flat Ta	abs	8		4	Truss Hea	ad Tapping Screws	8	8×2″	
Install Notes: Overlay Replacement ×							Drill × Cut ×					
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Open the hood., remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove the plastic filler panel from the top of the radiator support.						N/A					
3	Remove the four billet grilles from the box. The grilles will only fit in one direction. There is a top left, top right, bottom left and a bottom right grille. Test fit each one to ensure proper fit.						N/A					
4	Remove the mounting hardware from the box. Take the u-clip nuts and place one on each of the flat tabs over the hole.						N/A					
5	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.						N/A					
6	Reinstall the black plastic cover which was removed in step 2.						N/A					
7	Installation completed!!!						N/A					

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!