



# PATENT PRODUCT Grille Installation Instruction

Rev. 20211201

<b>Part#</b>	D65787C&J&S	<b>Application</b>	For 2006-2008 Ram 1500 With Logo Show/2006-2009 Dodge Ram 2500 /3500 With Logo Show
--------------	-------------	--------------------	---

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
<b>Parts List</b>	#1	Billet Grille	1	Stainless Steel	#3	Screws	8	6-32 x 1.5"
	#2	Metal Brackets	8		#4	Flange Nuts	8	6-32

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.	
3	Thread a Screw in each nut welded to the grille. From the rear, place a Metal Bracket on each Screw. Now thread a Flange Nut on each Screw.	
4	Make sure the insert is centered and tighten the hardware.	
5	Reinstall the plastic shroud with the fasteners removed in Step 2.	
6	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!