

Part#	GR04FFD71A/H		Application	For 2005-2007 Dodge Dakota				
Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	4	Aluminum	3	Truss Head Screws	16	6# - 32x2"
	2	Toggle Nuts	16	6#				
<b>Install Notes:</b> Overlay <input checked="" type="checkbox"/> Replacement <input type="checkbox"/> Drill <input type="checkbox"/> Cut <input type="checkbox"/>								
Step	Description			illustration				
1	Identify the grille & hardware with parts list.							
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.							
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.							
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb.			N/A				
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!							
6	Repeat steps four and five for the remaining three welded tabs on the billet grille.							
7	Install the others grille using the same steps as above.							
8	<b>Modify Latch</b> Add the latch mechanism extension. Place a ferrule on the 3/32 cable, and then feed 2 inches of the cable through the hole that is already in the latch. Now feed the cable back through the ferrule and crimp with the crimping pliers. At the opposite end of the cable place a ferrule on the cable, loop the cable around the cross of the grille frame, back through the ferrule, and finally crimping the ferrule tight. This extension will now be used for releasing your hood. See figure below:							
9	Reinstall the black plastic cover which was removed in step 2.							
10	Installation completed!!!							

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!