

PATENT PRODUCT Grille Installation Instruction

Rev. 20201201

Part#	D66471C&J&S Application		on F	For 2005-2007 Dodge Dakota							
	-	Item	Part Name		QTY	Description		Item	Part Name	QTY	Description
Parts L	ist	t #1 Billet Gr		ille	1	Stainless	Steel	#3	Truss Head Screws	16	6# - 32x2"
		#2 Toggle Nuts		16	6#						
Install Notes: Overlay \checkmark Replacement \times Drill \times Cut \times											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.										
3	Insert the screws into the weld tab hole from front side of the billet grille.										
4	Center the billet grille onto the OEM grille. Press & insert the Toggle Nuts on to the rear of the OEM grille through the gap.										
5	Modify Latch Add the latch mechanism extension. Place a ferrule on the 3/32 cable, and then feed 2 inches of the cable through the hole that is already in the latch. Now feed the cable back through the ferrule and crimp with the crimping pliers. At the opposite end of the cable place a ferrule on the cable, loop the cable around the cross of the grille frame, back through the ferrule, and finally crimping the ferrule tight. This extension will now be used for releasing your hood. See figure below:										
6	Make sure the insert is centered and tighten the hardware.										
7	Reinstall the plastic shroud with the fasteners removed in Step 2.										
8	Installation completed.										

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!