

Grille Installation Instruction

Rev. 150116

Part# GR04FFH70H Application 2011-2012 Dodge Avenger Main Upper

		Item	Part Name		QTY Description		Item		Part Name	QTY	Description	
Parts L	ist	1	Billet Grille		4	Aluminum		3	Tru	uss Head Screws	8	6-32×1″
	2 T		Toggle	Toggle Nuts		6#						
Install N	Note	lotes: Overlay		√ R	eplacement ×		D	rill [×	Cut ×		
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Remove grilles from the box and identify the top grille from the bottom grille.											
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.											
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb.											
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!											
6	Repeat steps three and four for the remaining seven welded tab on the billet grille.											
7	Please remove the logo trademark from OEM shell if necessarily.											
8	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!