

## PATENT PRODUCT Grille Installation Instruction

Rev. 171101

Part#		GR04FFI18J		Application For 2		011-2014 Dodge Challenger					
		Item	Part Na	me QTY	Descrip	otion	Item	Part Name	QTY	Description	
Parts L	ist	1	Billet Grille	1	Stainless ste	eel	3	Toggle Nuts	2	6#-32UNC	
		2 Stud		2	6#-32UNCX1	.5					
Install Notes: Overlay  Replacement ×						× Dr	ill ×	Cut [	X		
Step	Description					illustration					
1	Ider	ntify the	e grille & har	dware with pa	arts list.	#		5		la l	
2	Optional (for vehicles with black plastic cover under hood). Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.										
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb.										
5	Secure billet grille using the toggle nut from the back side of the OEM grille shell.					N/A					
6	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.					N/A					
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!