




Grille Installation Instruction

Rev. 190401

Part#	GR04GEC75T/H	Application	For 2002-2008 Dodge Ram Regular Model Tow Hook Must Be Removed Not For Iaramie SLT 4X4/Sport Model/Daytona
--------------	---------------------	--------------------	---

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Stainless steel	4	Studs	4	6-32 X1"
	2	Kept Nuts	4	6-32	5	Washers	4	
	3	2-Hole Tabs	4					

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.	
3	Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.	
4	Thread a stud in each nut welded to the grille. Thread a stud in each nut welded to the grille. Then push the studs through the grid of the shell and center the grille into the opening. You need mark and drill 4 holes. From the rear, place a tab on each stud. Now thread a nut and a washer on each stud. From the rear, place a tab on each stud. Now thread a nut and a washer on each stud.	
5	Make sure the insert is centered and tighten the hardware.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!