

Grille Installation Instruction

Rev. 190101

Part#	GR04GEG20T/H	Application	For 2002-2005 Dodge Ram
-------	--------------	-------------	-------------------------

Dowto Lint	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	4	Stainless steel	4	Nylon Lock Nuts	16	6-32
Parts List	2	Studs	16	6-32×2″	5	Washers	16	
	3	Flat Tabs	16					

Install N	lotes: Overlay $\sqrt{}$ Replacement \times	Drill × Cut ×				
Step	Description	illustration				
1	Identify the grille & hardware with parts list.					
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.					
3	Center the grille into the opening of the factory grille shell. Secure the stud to the welded nut on the back side of the grille. Be sure the bolts are through the OEM grille shell.					
4	From the rear, place a flat tab on each screw. Now thread a nylon lock nut and a washer on each screw.					
5	Make sure the grille is centered and tighten the fasteners.					
6	Reinstall the black plastic cover which was removed in step 2.					
7	Installation completed!!!					

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!