Grille Installation Instruction Rev. 1410												
Part#		GR04GFC39T					015-2016 DODGE Challenger Lower Bumper WITH PTOR CONTROL					
		Item	Part Nar	ne QTY	QTY Descrip		on	ltem	Part Name	QTY	Description	
Parts L			Mesh Grille					3	Lock Nut	8	6-32	
		2	Flat Tab	8	8 /		1	4	Stud	8	6-32X1"	
Install N	Note	es: Ov	verlay 1	Repla	cement	×	Dri		Cut	×		
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access to the rear of the grille shell.											
3	Cer	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
4	Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.									ock Nuts		
5	Mal	Make sure the grille is centered and tighten the fasteners.										
6	Rei	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!