

Grille Installation Instruction

Rev. 150116

Part#	GR04HED75H	Application	02~05 Dodge RAM Sport – Low Bumper Billet Grille
-------	------------	-------------	--------------------------------------------------

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
Parts Lis	1	Billet Grille	1	Aluminum	4	Lock Washers	2	1/4 "
Parts Lis	2	Hex Bolts	2	1/4" -20×3/4"	5	Nuts	2	1/4" ×20
	3	Flat Washers	2	1/4"				
Install Notes: Overlay Replacement								
Step	Description					illustration		

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	N/A
3	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille.Be sure the bolts are through the OEM grille shell.	N/A
4	Secure billet grille using the nuts from the back side of the OEM grille shell.	N/A
5	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.	N/A
6	Reinstall the black plastic cover which was removed in step 2.	N/A
7	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!