

Grille Installation Instruction

Rev. 190401

Part#	GR04IEC75A/H	Application	For 2002-2008 Dodge Ram Regular Model Tow Hook Must Be Removed Not For Iaramie SLT 4X4/Sport Model/Daytona
-------	--------------	-------------	---

	11		Ke	Removed Not For Iaramie SL1 4X4/Sport Model/Daytona							
		Item	Part Name	QTY	Description	Item	Part Name	QTY	Description		
Parts L	ist	1	Mesh Grille	1	Aluminum	3	K-Lock Nuts	4	6-32		
		2	Flat Tabs	4		4	Studs	4	6-32×1 1/2"		
Install Notes: Overlay											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.				ts list.						
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Now thread studs into the grille using a slotted screwdriver. Then push the studs through the grid of the shell and center the grille into the opening. You need mark and drill 4 holes.										
4	Fasten the grille use the tabs and the k-lock nuts from the rear.										
5	Make sure the grille is centered, but do not over-tighten.										
6	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!