

Grille Installation Instruction

Rev. 190501

Part#	GR04IFE19 A/H	Application	For 2007-2010 Dodge Avenger SXT Not For V6
-------	------------------	-------------	--

	lt	tem	Part Name	QTY	Description	Item	Part Name	QTY	Description		
Parts Li	st	1	Billet Grille	3	Aluminum	3	Studs	10	6-32×1.5″		
		2 K-Lock Nuts		10	6-32	4	Flat Tabs	10			
Install Notes: Overlay $\boxed{\hspace{1em}}^{\checkmark}$ Replacement $\boxed{\hspace{1em}}^{\times}$ Drill $\boxed{\hspace{1em}}^{\times}$ Cut $\boxed{\hspace{1em}}^{\times}$											
Step	Description				illustration						
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
	Now thread studs into the grille using a slotted screwdriver. Then push the studs through the grid of the shell and center the grille into the opening.										
4	Fasten the grille use the tabs and the k-lock nuts from the rear, but do not over-tighten.										
5	Make sure the grille is centered and tighten the fasteners, but do not over-tighten.										
6	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!