

## Grille Installation Instruction

Rev. 180301

Part#	G	GR04IFF13A/H			Application For 2 Only			2009-2012 Dodge Ram 1500 Honeycomb Style					
		Item Part Nam		e QT	QTY Descrip		ption	Item	Part Name		QTY	Description	
Parts L	iet	1	1 Billet Grille		А	luminum		4	Slotted Studs		16	6-32×1.5″	
i aits L	ist	2	Kep Nuts	16	6	-32		5	Flat Tabs		16		
		3	Washers	16	16								
Install N	Note	es: Overlay		Rep	Replacement		×	Drill	× C	ut ×			
Step	Description							illustration					
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.												
3	Now thread studs into the grille using a slotted screwdriver. Then push the studs through the grid of the shell and center the grille into the opening. Fasten the grille use the flat tabs, the kep nuts and washers from the rear, but do not over-tight.												
4	Make sure the billet grille is centered and tighten the fasteners.												
5	Reinstall the black plastic cover which was removed in step 2.												
6	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!