

PATENT PRODUCTGrille Installation Instruction

Rev. 20230201

Part#		DL5318P Application		For 2006-2008 Ram 1500 / 2006-2009 Dodge Ram 2500 / 3500										
		Item	Part N	lame	QTY		Desc	cription		Item	Part N	ame	QTY	Description
Parts Li	ict	#1 Mesh G		rille 1		Black Powder Coated S			d SS.	#4	Square head Bolts		6	
raits Li	iSt	#2	#2 Flange Nuts		6	M6*	20		#5	Screws		6	M6	
		#3 Flat Washers		shers	6	6 M6								
Install Notes: Overlay X X X Replacement √							$\sqrt{}$	Dril	I ×	Cut	×			
Step	Description							illustration						
1	Identify the grille & hardware with parts list.													
2	Using a 8mm socket locate and remove 6 factory bolts securing the upper portion of the factory grille onto vehicle. Discard factory hardware.													
3	Using a 8mm socket locate and remove 6 factory bolts securing the lower portion of the factory grille onto vehicle. Discard factory hardware.													

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation.

Thank you for choosing our product!



Installation completed.

8

PATENT PRODUCTGrille Installation Instruction

Rev. 20230201

Part#	DL5318P Application		For 2006-2008 Ram 1500 / 2006-2009 Dodge Ram 2500 / 3500						
4	Close the vehicle hood. Firmly grab and pull factory grille off of vehicle. Set factory grille aside in a protected area.								
5	Slide (6) Square head bolts on the upper portion as shown below.								
6	Place the grille onto vehicle. Open the vehicle hood. Secure with (6) flange nuts. Repeat for remaining bolts and flange nuts.								
7	Place screws with flat washers through the factory holes and onto the grille (lower portion). Tighten down screws with a screw driver.								

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation.

Thank you for choosing our product!