Grille Installation Instruction

Part#	G	R06C	FJ14H	Ар	plication	on	For	or 2005-2009 Ford Mustang GT V8 Not For California Edition							For California
		Item Part Nar		me	QTY	Descrip			otion		em	Part Name		QTY	Description
Parts L	ict	1	Mesh Gril	le	3	Stain	nless s	teel			4	K-Lock Nuts		8	6-32
Faits L	131	2	Studs		2	6-32× 2″					5	Washers		2	
		3	Studs		6	6-32:	× 1″				6	Nylon Washer	S	6	
Install N	Vote	es: Ov	erlay	\checkmark	Repla	icement 🕞		×	Dr	ill	×	Cut	×		
Step	Description								illustration						
1	Identify the grille & hardware with parts list.														
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.														
3	Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.														
4	Thread a stud in each nut welded to the grille. Then thread a nut and a washer on each stud.														
5	Make sure the grille is centered and tighten the fasteners.														
6	Reinstall the black plastic cover which was removed in step 2.														
7	Installation completed!!!														

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!