

PATENT PRODUCT Grille Installation Instruction

Rev. 130701

| Part# | GR06FEA52A | | | ١ | Application | | | 7~09 Ford Edge – Billet Grille | | | | | | |
|--------------------------------------|--|-------------|-------------|---|-------------|------------|----------|--------------------------------|--------------|-------|-----------|-------|-----|-------------|
| | | Item | Part N | | ame | QTY | Des | cripti | ion | Item | Part Name | | QTY | Description |
| Parts Li | st | 1 | Billet Gril | |) | 1 | 6 Billet | ts | | 3 | Speed | Clips | 2 | 8# |
| | | 2 | Screws | | | 2 | 8#×3/ | 4" | | | | | | |
| Install Notes: Overlay × Replacement | | | | | | √ <u> </u> | Drill | √ |] (| Cut × | | | | |
| Step | | Description | | | | | | | illustration | | | | | |
| 1 | Identify the grille & hardware with parts list. | | | | | | N/A | | | | | | | |
| 2 | Remove all of the plastic push clips and bolts that attach the upper portion of the front fascia to the core support. | | | | | | | N/A | | | | | | |
| 3 | Remove all of the small bolts from the inner fender well. Figure 1 . | | | | | | | r | | | | 7 | | |
| 4 | Once all of the bolts and clips have been removed, rock the entire front fascia forward. Figure 2 | | | | | | - | | | | | | | |
| 5 | The black plastic section that is attached to the backside of the front fascia will need to be removed by pushing the metal clips from the openings. Figure 3 | | | | | | | | | | | | | |
| 6 | The chrome grille face will need to be separated from the black plastic section that was removed in step 5. | | | | | | N/A | | | | | | | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



PATENT PRODUCT Grille Installation Instruction

Rev. 130701

| | | I | 1 | |
|-------|--|------------------------|----------|-------------------------------|
| Part# | GR06FEA52A | Application | 07- | ~09 Ford Edge – Billet Grille |
| 7 | Once the chrome gr removed reattach th to the front fascia us hardware. | e black plastic sect | tion | N/A |
| 8 | Gently rotate the fro original position. You the front fascia at the | u will not fully attac | the h | N/A |
| 9 | Center the small cer the opening and ma mounting holes. Fig | rk and drill the | nto | |
| 10 | Re-center the small and attach to the bu clips and screws. Fi | mper using the spe | | |
| 11 | Re-attach the front f using the factory har steps 2 and 3. | | | N/A |
| 12 | Installation completed! | !!! | | N/A |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!