

PATENT PRODUCT

Grille Installation Instruction

Rev. 190801

7001	TO PARTS SPE	CIALIST INC				0		1101.	190001	
Part#	F65356C/S/J		Application Lariat/Ha Lariat/Ha Lariat/Ha		-2007 Ford Excursion /2005-2007 Ford F-250 Not For arley Davidson/2005-2007 Ford F-350 Not For arley Davidson/2005-2007 Ford F-450 Not For arley Davidson/2005-2007 Ford F-550 Not For arley Davidson					
	It	tem	Part Nan	ne QTY	Description	Item	Part Name	QTY	Description	
	1		Billet Grill	e 1	1 Stainless steel		'L' BracketBottoms	2		
Parts L	ist	2 U-Clip Nu		ts 4	4 8#		Truss Socket Tapping Screws	4	8×1″	
		3 Hex Bolts		2	1/4" -20×3/4"	7	Flat Washers	4	1/4"	
		4	Nuts	2	1/4″ -20					
Install N	Notes	otes: Overlay V Replacem			placement ×	Dri	II × Cut ×			
Step	Description					illustration				
1	Identify the grille & hardware with parts list.									
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.									
3	Slide the U-clip nuts onto the 'L' brackets provided. Center the U-clip nuts over the smaller sets of holes. Note the tabs welded to the rear of the billet. There are two tabs in the center and two along the bottom. As shown in the diagram; fasten the brackets to the billet using the 1″ screws. Do not tighten the screws completely at this time.									
4	brack 'L' bump secur The b	ets in shape er. Us e the racke	billet into th to the openi ed brackets se the 1/4" short end o ets are made oper alignme	ng first. The mount to factorial to factoria		۵.				
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.									
6	Reins	Reinstall the black plastic cover which was removed in step 2.								
7	Installation completed!!!									

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!