1		
	P	5
AUTO PARTS SPEC	ALIST INC.	

Grille Installation Instruction

Part#	GR06FEG25A/H Application For 2004-2008 Ford F-150 Honeycomb Style Not For FX2/FX4 and King Ranch Model										
		ltem	Part Nam	ne	QTY	Descript	ion	ltem	Part Name	QTY	Description
Parts L	ist	1	Billet Grille		1	Aluminum		3	Socket studs	4	1/4″ -20×11/2″
2 U Brackets 4						4	Nylon Lock Nuts	4	1/4″-20		
Install Notes: Overlay \checkmark Replacement \times Drill \times Cut \times											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Remove Ford Emblem by removing the 2 nuts (10mm) on the back side of the grille. Then push the 2 studs out through the front of the grille shell.										
4	Place the billet grille into the front of the factory grille and center in opening.										
5	Using the supplied hardware, place the stud through the front opening with the bracket and lock nuts on the back.										
6	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.										
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!