

Grille Installation Instruction

Rev. 150116

Р	art#	GR06FEG26C	Application	For 04~08 Ford F-150 – Bar Style (Not for FX2 Model)
---	------	------------	-------------	--

		Item	n Part Name		QTY Descript		ription	tion Item		Part Name	QTY	Description	
Parts L	.ist	1	Billet Grille		1	Stainle	ss steel	el 3		Truss Head Screws	14	6-32×1.5″	
		2	Toggle Nuts		14	6#							
Install I	Notes: Overlay			Replacer	nent	×	Orill [×	Cut ×				
Step	Description							illustration					
1	Ider	ntify the	grille &	hardware v	vith parts l	ist.	7				<u> </u>		
2	OÉI	M grille	/ front pa	the black p anel) from of the grille	vehicle. Th								
3	First let us install middle grille, place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.												
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honey comb.												
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!						en.			nut	billet	grille	
6	Then center side billet grille in factory grille shell. Place the screw through the holes billet grille and the factory grille.							screw					
7	Place the supplied tabs and nuts on backside of factory grille as shown above and tighten.							factory grille shell					
8	Installation completed!!!						N/A						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!