





Grille Installation Instruction

Rev. 150116

Part#	GR06FEG26H	Application	04~08 Ford F-150 – Bar Style (Not for FX2 Model)
-------	------------	-------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Truss Head Screws	14	10-24 × 1.5"
	2	Toggle Nuts	14	10#				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	N/A
	First let us install middle grille, place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.	N/A
	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honey comb.	N/A
3	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!	
4	Then center side billet grille in factory grille shell. Place the screw through the holes billet grille and the factory grille.	
5	Place the supplied tabs and nuts on backside of factory grille as shown above and tighten.	
6	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!