

Part#	GF	GR06FEG26S		Application		on <b>F</b>	for 04~08	8 For	'd F-1	50 – Bar Si	tyle ( I	Not for	r FX2 Model )	
		ltem	Pa	rt Na	me	QTY	Descrip	tion	Item	Part Na	me	QTY	Description	
Parts L	ist	1	Billet	Grille		1	Stainless s	teel	3	Truss Head	Screws	14	6-32×1.5″	
		2	Toggle Nuts		6	14	6#							
Install Notes: Overlay $\checkmark$ Replacement $\times$								) C	Drill 🗦	Cut	×			
Step		Description							illustration					
1	Identify the grille & hardware with parts list.											H		
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.													
3	First let us install middle grille, place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.													
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honey comb.							N/A						
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!									nut			grille	
6	Then center side billet grille in factory grille shell. Place the screw through the holes billet grille and the factory grille.								screw					
7						s on bac nd tighte	ckside of n.	factory grille shell						
8	Installation completed!!!													

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!