




Grille Installation Instruction

Rev. 180701

Part#	GR06FEG29A/H	Application	FOR 1997-1998 Ford Expedition Bar Style/ 1997-1998 Ford F-150 Bar Style/ 1997-1998 Ford F-250 Light Bar Style Except Lariat
-------	--------------	-------------	---

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Aluminum	3	U-Clip Nuts	6	8#
2	Screws	6	8# X 2"	4	"J" Hook Tabs	6		

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.	
3	Test fit the 2-piece grille into the grille shell. They are not interchangeable.	
4	Fix the U-clip nuts onto the tabs, make sure the holes of the nuts match those of the tabs, then use "J" hook tabs the shell bar and put the screws through the front side of the billet grille and then the grille shell and then through the tabs.	
5	Make sure the grille is centered and tighten the fasteners.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
We are not responsible for any damage caused by the installation. Thank you for choosing our product!