

Τ

Part#	GR06FEG38H		Application		1997-1998 Ford Expedition With Logo Show						
		ltem	Part Name		QTY	Descrip	tion	Item	Part Name	QTY	Description
Parts L	ist	1	Billet Gr	ille	1	Aluminum		3	Truss Head Tapping Screws	4	8# × 2 ″
		2 U-Clip N		uts 4		8#		4	Flat Tabs	4	
Install Notes: Overlay \checkmark Replacement \times								Drill ×	Cut ×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Make sure you have room to work from the backside of the grille shell, or you may take the grille shell off to work on.										
4	Fix the U-clip nuts onto the tabs, make sure the holes of the nuts match those of the tabs, then Put the screws through the front side of the billet grille and then the grille shell and then through the tabs.						N/A				
5	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.						N/A				
6	Re-install the whole shell back onto your vehicle.						N/A				
7	Installation completed!!!						N/A				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!