

PATENT PRODUCT Grille Installation Instruction

Rev. 130901

| Part# | # | GR | 06FEH00 | J For | 04~08 | Ford F | -650 / 75 | 50 - Bi | llet Grille | | | |
|---------------|---|----------|---------------|-------|---------|----------|-----------|--------------|-------------|-------|-------------|--|
| | | ltem | Part N | lame | QTY | Des | cription | Item | Part Name | QTY | Description | |
| Part: List | | 1 | Billet Grille | | 5 | Stainles | s steel | 3 | Screw A | 4 | 8#×2 1/2" | |
| | | 2 U-Clip | | 16 | 8# | | 4 | Screw B | 12 | 8#×2" | | |
| Instal | l No | otes: (| Overlay [| | Replace | ement | × | Drill | × Cut | × | | |
| Step | Description | | | | | | | illustration | | | | |
| 1 | Identify the grille & hardware with parts list. | | | | | | | | | | | |
| 2 | Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. | | | | | | | | | | | |
| 3 | Center the billet grille into the opening of the factory grille shell. | | | | | | | | | | | |
| 4 | Secure billet grille using the U-Clips & screws from the back side of the OEM grille shell. | | | | | | | | | | | |
| 5 | Make sure the billet grille is centered and tighten the fasteners. | | | | | | | | | | | |
| 6 | Reinstall the black plastic cover which was removed in step 1. | | | | | | | | | | | |
| 7 | Installation completed!!! | | | | | | | | | | | |
| | The instruction here is for your reference only. You may need to here the grille a little bit to | | | | | | | | | | | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!