

Grille Installation Instruction

Rev. 180801

Part#	GR06FFD46A/H A		Арр	olicatio	For 20 logo s		017 Ford Mustang Only for V8 GT models with				
		Item	Part Name		QTY	Descrip	tion	Item	Part Name	QTY	Description
Parts Lis	st	1	Billet Grille		3	Aluminum		3	Screws	8	6-32X1.5"
		2	Toggle Nuts		8	6-32					
Install Notes: Overlay $\boxed{\hspace{1em}}$ Replacement $\boxed{\hspace{1em}}$ Drill $\boxed{\hspace{1em}}$ Cut $\boxed{\hspace{1em}}$											
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
	Hold the billet grille against the OEM grille shell, center and mark holes for drilling. Remove billet grille and drill holes according to your mark.										
	Center the grille into the opening of the factory grille shell. Place screws through the welded aluminum tabs on the front of the grille. Be sure the screws are through the OEM grille shell.										
5	Secure the grille using the toggle nut from the back side of the OEM grille shell. Mark and drill 6 holes Mark and drill 6 holes									72-0026-72	
6	Make sure the billet grille is centered and tighten the fasteners.										
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!