



# PATENT PRODUCT Grille Installation Instruction

Rev. 20201101

<b>Part#</b>	F66882C&J&S	<b>Application</b>	For 2011-2013 Ford Fiesta SE Hatch Back/ SEL Hatch Back/2013 Ford Fiesta Titanium Hatch Back
--------------	-------------	--------------------	--

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
<b>Parts List</b>	#1	Billet Grille	1	Stainless Steel	#3	U-Clip Nuts	4	#8
	#2	Screws	4	#8- 2"	#4	Flange Offset	4	2"

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.	
3	Place the #8 U-Nut to the 2' Flange Offset as shown.	
4	Place the 2' Screws in the holes on the billet bumper and have the 2' Flange hooks facing towards the grille. Place the billet grille over the factory bumper and turn the 2' Flanges sideways so they will go through. Once the 2' Flanges hook on the factory bumper. with another screwdriver or anything that will go through, tweak the Flanges and hold them in place then start to tighten the 2' Screws for all four.	
5	Reinstall the plastic shroud with the fasteners removed in Step 2.	
6	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!