

Grille Installation Instruction

Part#		GR06GEG22 T/H		Application		on L	For 1999-2003 Ford F-150 Main Upper Bar Style With Logo Show/1999-2003 Ford F-150 Harley Davidson Bar Style With Logo Show/1999-2003 Ford F-150 Lightning Bar Style With Logo Show							
		Item Part Na		me	QTY Desc		escription		Item	Pa	art Name	QTY	Description	
Parts Li	st	1	Mesh Grille		1 Stainles		less steel		3	Hex F	-lange Nut	6	0.138-32	
		2	Flat Tab		6				4	Stud		6	0.138-32×2″	
Install N	otes: Overlay 🗸 Replacement						nt ×		Drill	×	Cut	×		
Step	Description							illustration						
1	Identify the grille & hardware with parts list.													
	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.													
3	Secure the stud to the threaded holes on the rear of the grille.													
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.													
5	Secure grille using the flat tabs and hex flange nuts from the back side of the OEM grille shell.													
6	Make sure the grille is centered and tighten the fasteners.													
7	Rei	Reinstall the black plastic cover which was removed in step 2.												
8	Installation completed!!!													

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!