

PATENT PRODUCT Grille Installation Instruction

Rev. 20220301

| Part# | F | F75077K&S | | Applicat | ion | For 2021-Up Ford F-150 XL/ XLT | | | | | |
|--|--|--|-------------------|---|----------|--------------------------------|--------|-------------|-----|-------------|--|
| | | Item | Pa | rt Name | QTY | Description | Item | Part Name | QTY | Description | |
| Parts L | ist | #1 | Mesh G | rille | 1 | Stainless Steel | #4 | Washers | 4 | | |
| - 4110 2101 | | #2 Studs | | | 20 | #6-32 | #5 | Tabs | 8 | | |
| | | #3 | Hex Fla | nge Nuts | 20 | #6 | #6 | 2-Hole Tabs | 4 | | |
| Install Notes: Overlay ✓ Replacement × Drill ✓ Cut × | | | | | | | | | | | |
| Step | | Description | | | | illustration | | | | | |
| 1 | Ider | ntify the | e grille & | hardware with | parts li | rts list. | | | | | |
| 2 | Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual. | | | | | | | | | | |
| 3 | Hold the grille against the OEM grille shell, center and mark (4) holes for drilling. Remove grille and drill holes according to your mark. | | | | | | | | | | |
| 4 | Thread a Stud in each nut welded to the grille. From the rear, place a Tab on each Stud. Now thread a Hex Flange Nut on each Stud. | | | | | | | | | | |
| 5 | Mak | se sure | (4) (4) (4) | illing Studs Hex Flange No Washers | | |) Tabs | ange Nuts | | | |
| 6 | Rei | Reinstall the plastic shroud with the fasteners removed in Step 2. | | | | | | | | | |
| 7 | Installation completed. | | | | | FESSIVA FESSIVA | | | | | |

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!