

Grille Installation Instruction

Rev. 180801

Part#		GR06GFD02T/H		Application		For 2015-2017 Ford Mustang Only for V6 Base models					
		Item	Part Name QTY		Description		Item	Part Name	QTY	Description	
Parts L	ist	1	Mesh Grille	1	Stainless steel		3	Studs	6	0.138-32UNCX1.5"	
		2	Flange Nuts	6	0.138-3	32UNC	4	Flat tabs	6		
Install Notes: Overlay $\boxed{\hspace{1em}}$ Replacement $\boxed{\hspace{1em}}$ Drill $\boxed{\hspace{1em}}$ Cut $\boxed{\hspace{1em}}$											
Step			Descript	ion			illustration				
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.										
4	Secure the stud to the threaded holes on the rear of the grille. Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
5	Secure the grille using the flat tabs and flange nut from the back side of the OEM grille shell. Mark and drill 3 holes Mark and drill 3 holes										
6	Ma	Make sure the grille is centered and tighten the fasteners.									
7	Rei	Reinstall the black plastic cover which was removed in step 2.									
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!