

Grille Installation Instruction

Rev. 181201

Part#	GR06GFD05T/H App.					lication	For 2015-2017 Ford Mustang Only for V8 GT models Lower Bumper					
		Item	Part Name			QTY	Description		Item	Part Name	QTY	Description
Parts L	ist	1	Mesh Grille		1	Stainless Steel		3	Screws	6	8# X 3/4"	
		2 U-Clip Nuts			6 8#							
Install N	Note	es: Ov	erlay		Re	placen	nent	× Dr	iII	Cut	×	
Step	Description illustration											
1	Identify the grille & hardware with parts list.											
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3	Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.											
4	Install the U-Clip Nuts onto the tabs on the back side of the mesh grille.											
5	Hold the grille up to the opening of the factory shell. Secure the grille using the screws from the back side of the OEM grille shell. Screws										Screws	
6	Make sure the billet grille is centered and tighten the fasteners.											
7	Reinstall the black plastic cover which was removed in step 2.											
8	Installation completed!!!									-		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!