

5 6

7

Installation completed!!!

Grille Installation Instruction

Rev. 181101

Part#	GR06GFD07T/H			Application		, ,	For 2018-2019 Ford Mustang Only for EcoBoost models Lower Bumper							
		Item	Part Name		QTY	QTY Descri		otion	Item	Part Nam	e Q	TY	Description	
Parts L	ist	1	Mesh Grille		1	Stainless S		Steel	3	Studs		6	0.138-32 X 1.5"	
	2		Flange Hex Nuts		6	0.138-32			4	Flat tabs		3		
Install N	Note	lotes: Overlay		Re	Replacen		nent × Dr		II \[\sqrt{1}	Cut	×			
Step	Description							illustration						
1	Identify the grille & hardware with parts list.													
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.													
3	Thread a stud in each nut welded to the grille. Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.													
4	and	Secure the grille using the flat tab and flange hex nut from the back side of the OEM grille shell.						2	Luo/A	Mark and d	o la		(6) 1.5" Studs (3) Flat tabs (3) Flange Hex Nuts	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

Make sure the grille is centered and tighten the fasteners. But not over-tighten.

Reinstall the black plastic cover which was removed in step 2.