

Installation completed!!!

## PATENT PRODUCT Grille Installation Instruction

A	Grille Installa							ation Instruction					Rev. 200801		
Part#	GR06HEC88C Applicat				Duty	/199	4 Ford Excursion /1999-2004 F 9-2004 Ford F-350 Super Dut 50 Super Duty /1999-2004 For					y /199	99-2004		
	Item	Par	t Name	QTY	Descri	ption	Item		Part Nan	ne		QTY	Description		
	1	Billet	Billet Grille L Shape Tab		Stainless	steel	4	Truss Socket Tapping Screws		ews	4	10×3/4"			
Parts Lis	st 2	L Sha					5	Truss Socket Tapping Screws			ews	4	10×1″		
	3	U-Clip Nuts		8	10#		6	Kep Nuts				4	1/4" ×20		
							7	Hex Bo			4	1/4" -20x3/4"			
Install N	lotes: O	verlay	×	Repla	cement	V	Dri	I ×	Cut	×					
Step	Description						illustration								
1	Identify the grille & hardware with parts list.														
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove license plate holder from bumper.														
3	Start with the center piece installation. Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille. Be sure the bolts are through the OEM grille shell.														
4	Secure billet grille using the U-Clip Nuts from the back side of the OEM grille shell.														
5	Continue to side grille pieces. Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille. Be sure the bolts are through the OEM grille shell.														
6	Drill and attach shorter L brackets go towards outside of bumper with flat screws provided.														
7			et grille is o do not ove			en					1	mirror t	for other side		
8	Reinstall in step 2.	the black	plastic co	ver whic	h was rem	noved							1		
									finished	d grille in bu	umper				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!