

Grille Installation Instruction

Part#	GR0	R06HFC10T/U Application		For 2015-2017 Ford F-150 Main Upper							
	Item	Part Name		QTY		cription	ltem		Part Name	QTY	Description
Parts List	t 1 2	Billet Grille Nylon Lock Nuts		1 8	Alum 10-24	iinum	3	Fender V	Vashers	8	
Install No			Rep	lacem			Drill ×		Cut ×		
Step		Descriptio	n			illustration					
	ldentify list.	the grille & hard	ware	e with	parts						
	Turn off engine and chalk tires with stop block . Optional (for vehicles with black plastic cover under hood), Open Hood.						iood), Open				
3 Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.											
4	Remove plastic shroud and then set aside for reinstallation later.										
									EB 3		
5		ou will need to co							mpletely. The plast		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Grille Installation Instruction

Part#	GR06HFC10T/U	Application	For 2015-2017 Ford F-150 Main Upper				
	FIG 4		Image: Window Wi Window Window Wind				
6	On each side of the factor corner just outside and be (1) 8mm bolt on each side remove the (2) bolts.	whind, there is (1) 8mm bolt,				
7	On top of the core support, remove (4) 8mm bolts.						
8	Remove (4) plastic clips on upper corner near head lamp.						
	FIG 7		FIG 8				
9	Located next to the hood located at the top center plastic cable support clip.	er of grille. Not					
10	The OEM Factory Grille should now be free and ready to remove. Carefully place the grille on a soft cushioned surface and prepare to remove the shutter component which is currently fastened to the backside of the factory grille.						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#		GR06HFC10T/U	Application	For 2015	-2017 Ford F-150 Main Upper
11	0	emove the (7) 10mm pla utside edge and the (1) & enter structure.			FIG 10
12	R	emove the (4) plastic cli	ps located on th	e top lip.	FIG 11
13		et factory grille aside an rille.	d prepare to ins	stall your new	FIG 12
14	fix aı th	ked bolt thread. There is nd onto the mounting po	s 8 total. Place bints. Tighten do tructure.3) Flip	the provided a own with your up and stand	shioned surface.1)Fit the shutter component over each B/16" fender washer and nylon lock nut hardware over 7mm socket. 2)Make sure to reinstall the (1) 8mm bolt the entire grille unit up to access top.Re-insert plastic Brille.
FIG	13		FIG14		FIG15 FIG16

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06HFC10T/U	Application	For 2015-2017 Ford F-150 Main Upper			
15	Grille assembly is now ready to reinstall on vehicle. Match it up to factory mounting points and reinstall in the reverse order that the grille was removed. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts located near the bottom corners.					
	FIG17		FIG18			
16	Plug the (2) sensor connections back into the shutter component sensor units. Place plastic radiator shroud cover over core support making sure the cold air intake lip is overlapped on top of the shroud. Align the factory mounting holes and use the (10)plastic clips to secure and fasten in position.					
17	with 8 tab fasteners and the inside wheel well lip.	hen firmly press	th plastic body panel around the head lamp area making sure to align is into place. Use the (2) bolts to mount and secure the panel on the ers, reinsert the plastic tabs. (1) on each side.			
18	At this point you want to look over your work and examine the gap alignments around all edges and in between the new Grille and the vehicle components and body lines. Carefully close the hood for a complete visual inspection. If adjustment is needed, you can loosen the top mounts and shift side to side even gaps.					
19	Installation completed!!!					

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.