







| | | | |
|-------|------------|-------------|-------------------------------------------------------------|
| Part# | GR06HFD14F | Application | For 2009-2014 Ford F-150 Not For Harley Davidson And Raptor |
|-------|------------|-------------|-------------------------------------------------------------|

| Parts List | Item | Part Name | QTY | Description | Item | Part Name | QTY | Description |
|------------|------|-----------------|-----|-------------|------|-----------------|-----|--------------------------------------|
| | 1 | Billets | 11 | Aluminum | 7 | Back Bracings | 5 | |
| | 2 | Screws | 6 | 10# | 8 | Chromed Bolts | 55 | Fasteners for billet grille assembly |
| | 3 | Flat Nuts | 6 | 10# | 9 | Nylon Lock Nuts | 55 | Fasteners for billet grille assembly |
| | 4 | Studs | 2 | 6#×1 1/2" | 10 | Allen Key | 1 | Tool for fastening Chromed Bolts |
| | 5 | Lock nuts | 2 | 6# | 11 | Wrench | 1 | Tool for fastening Nylon lock Nuts |
| | 6 | Flange Brackets | 2 | | | | | |





| | | | | |
|----------------|----------------------------------|-------------------------------------------------|-------------------------------------------|-----------------------------------------|
| Install Notes: | Overlay <input type="checkbox"/> | Replacement <input checked="" type="checkbox"/> | Drill <input checked="" type="checkbox"/> | Cut <input checked="" type="checkbox"/> |
|----------------|----------------------------------|-------------------------------------------------|-------------------------------------------|-----------------------------------------|

| Step | Description | illustration |
|------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Identify the grille & hardware with parts list. |   <p style="text-align: center;">Front</p>  <p style="text-align: center;">Rear</p> |

| | |
|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2 | <p>Remove 6 Bolts along the top of the Grille Shell.(Fig 1)</p> <p>Remove 2 Clips along the Vehicle Support Bar.(Fig 2)</p> <p>Place the Plastic Pry-bar in between the Grille Shell and Hood ,Firmly start nudging away the Grill Shell from the Hood.(the Grille Shell is latched on with Clips).(Fig 3)</p> |
|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

| Part# | Application | For 2009-2014 Ford F-150 Not For Harley Davidson And Raptor | |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Step | Description | illustration | |
| 3 | With a Die Grinder, Remove the Vertical and Horizontal Plastic Bars that are around the Grille. (Fig 4 & 5) |  |  |
| 4 | Center the grille in backside of grille shell. Place the Grille into the Grille Opening. (Fig 6) |  | |
| 5 | With the 3/16 Drill, Drill through the Brackets and place the #10 Screws through them Threading with a Flat nut (Fig 7) . Thread a stud in each nut welded to the grille. Secure grille using the flange bracket and lock nuts from the back side of the OEM grille shell. |  | |
| 6 | Make sure the billet grille is centered and tighten the fasteners. | | |
| 7 | Installation completed!!! | | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!