

PATENT PRODUCT

4	AUTO PAI	RTS SPECIALIST	INC.		Gi	ille ms	lall	alion	Instruction		Rev	/. 200601	
Part#	GR06HFF14J Application For 2009-2014 Ford F-1		ord F-150 Not For I	Harley E	Davids	son And							
		Item	Part Name		QTY	Description		Item	Part Name		QTY	Description	
		1	Billet Grille		2	Stainless steel		6	Flange Brackets		2	2"	
Parts Li	ict	2	U-Clip Nuts		2	8#		7	Truss Socket Tapping Screws		2	8#×1"	
raits Li	3		Screw		6	10#		8	Lock nut		2	6#	
	4		Flat Nut		6	10#		9	Flange Bracke	ts	2	/	
		5 M-Scre		crew	2	6#×1 1/2"							
Install Notes: Overlay × Replacement √							V	Drill	$\sqrt{}$ Cut $\sqrt{}$				
Step	Description							illustration					
	Identify the grille & hardware with parts list.												
	Start from the upper piece. Remove 6 Bolts along the top of the Grille Shell.(Fig.1) Remove 2 Clips along the Vehicle Support Bar.(Fig.2) Place the Plastic Pry-bar in between the Grille Shell and Hood ,Firmly start nudging away the Grill Shell from the Hood.(the Grille Shell is latched on with Clips).(Fig.3)												
	With a Die Grinder, Remove the Vertical and Horizontal Plastic Bars that are around the Grille. (Fig. 4 & 5)Center billet grille in backside of grille shell. Place the Grille into the Grille Opening. (Fig. 6)												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

Fig 5

Fig 6



PATENT PRODUCT Grille Installation Instruction

Rev. 200601

Part# GR06HFF14J Application For 2009-2014 Ford F-150 Not For Harley Davidson And Raptor

With the 3/16 Drill, drill through the Brackets and place the #10 Screws through them Threading with a Flat nut. (Fig. 7) Place the M-Screws through the two inner Brackets that are on the Grille, the Flange Brackets and Thread with Nylon Lock Nuts. (Fig. 8)

4



The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



PATENT PRODUCT Grille Installation Instruction

Rev. 200601

Part#	GR06HFF14J	Application	For 2009-2014 Ford F-150 Not For Harley Davidson And Raptor							
5	Move on to the bumper piece. Remove the factory license plate holder. Next insert the billet grille into the bumper opening. Make sure the side of the billet grille with the two small metal tabs that extend down and away from the grille are on the bottom. (Fig 1) The two tabs will slide into a slot in the plastic on the bottom edge of the bumper opening. (Fig 2)									
6	On the bottom edge of the factory bumper are two metal tabs with holes. With the billet grille inserted into the bumper opening take two #8 screws and put them up through the billet grille tabs and the tabs with holes on the bottom edge of the factory bumper. Use a U-Clip nut secured on the flange bracket on the top side of the bumper tabs and tighten with a phillips screwdriver. (Fig 3)									
Fig 1	Make sure the billet gri	Fi elle is centered and	Fig 3 d tighten the fasteners. Installation completed.							

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!