




Grille Installation Instruction

Rev. 190601

Part#	GR06HFJ05A/H	Application	For 1994-1998 Ford Mustang Logo Area Trimmed
--------------	--------------	--------------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	4	Hex Bolts	2	1/4" -20x3/4"
	2	Tabs	1		5	Flat Washers	4	1/4"
	3	Nuts	2	1/4" -20	6	Lock Washers	2	1/4"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Open hood. Remove four black plastic screws attaching top cover. Remove plate.	
3	Remove bracket and pony emblem using star wrench.	
4	Place new grille into mounting position, aligning two holes in top of grille and securing with 7/16" bolts provided in hardware kit. Tighten securely.	
5	Re-install top cover plate removed in Step 2. Attach pony or cobra emblem using quality double-sided tape (3M or equivalent.)	
6	On 1994-1995 models, attach bracket provided to existing factory latch. On 1996-1998 models, bracket is not necessary.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!