

Grille Installation Instruction

Rev. 190601

Part#	G	R06LI	EG12H A	Application Style/1			99-2003 Ford F-150 Main Upper Honeycomb 999-2003 Ford F-150 Harley Davidson Honeycomb 999-2003 Ford F-150 Lightning Honeycomb Style						
		ltem	Part Name	QTY	Descri	ption	Item	F	Part Name	QT	Y	Description	
Parts L	ist	1	Rivet Grille	1	Stainless s	steel	3	Loc	Lock Nut			0.190-24	
		2	Flat Tab	6			4	Stu	Stud			0.190-24×2″	
Install N	Note	es: Ov	verlay 🗸	Repla	Replacement ×		Drill	×	Cut	×			
Step	Description						illustration						
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.												
3	Secure the stud to the threaded holes on the rear of the grille.												
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.												
5		Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.											
6	Ма	Make sure the grille is centered and tighten the fasteners.											
7	Rei	Reinstall the black plastic cover which was removed in step 2.											
8	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!