

Grille Installation Instruction

Part#	G	GR06LEG13H						99-2003 Ford F-150 Main Upper Harley Davidson 2003 Ford F-150 Lightning /1999-2003 Ford F-150 Bar						
		ltem	Item Part Na		QTY	Desc	cription	Item	Part Name		QT	Y	Description	
Parts L	ict	1	Rivet Grille		1	Stainless steel		4	Hex Flange Nut		3	0).190-24	
Fails L	151	2	2 Flat Tab		3			5	Stud		3	0).190-24×3″	
		3 Screws			3	8# x 3/4"		6	Flat tabs		3	8	3#	
Install N	Note	lotes: Overlay			Repla	acement ×		Drill		Cut	×			
Step			Des	cript	ion	on illustration								
1	Identify the grille & hardware with parts list.													
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.													
3	Secure the stud to the threaded holes on the rear of the grille. Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.													
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.													
5	nut	Secure grille using the flat tabs , hex flange nuts ,screws and flat nuts from the back side of the OEM grille shell.												
6	Ma	Make sure the grille is centered and tighten the fasteners.												
7	Rei	Reinstall the black plastic cover which was removed in step 2.												
8	Inst	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!