

Grille Installation Instruction

Part#	GR06L	.FC10G	Applicat	tion	2015-2016	Ford H	-150 Main Upper		
	ltem	Part	Name	QTY	Description	ltem	Part Name	QTY	Description
Parts Lis	1	Mesh Grille	;	1		4	Fender Washers	7	
	2	"Z" Bracket	ts (Long)	2		5	Nylon Lock Nuts	12	10-24
	3	"Z" Bracke	ets (Short)	3					
Install Notes: Overlay \times Replacement $$ Drill \times Cut \times									
Step	Description				illustration				
1	Identify the grille & hardware with parts Ist.								
2	Turn off engine and chalk tires with stop block . Open Hood.								
3	Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.								
4	Remove plastic shroud and then set aside for reinstallation later.								
	FIG 1			FIG	2				
5	On the ir	ou will nee		el well	lip, remove (2)		s. The headlight plastic bo move completely. The pla		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Grille Installation Instruction

Part#	GR06LFC10G	Application	2015-2016 F	ord F-150 Main Upper	
6	On each side of the factory grille near the bottom corner just outside and behind, there is (1) 8mm bolt, (1) 8mm bolt on each side. Use 8mm socket to remove the (2) bolts.				
7	On top of the core s	support, remove (4	4) 8mm bolts.		
8	Remove (4) plastic	clips on upper co	rner near head lam	ıp.	
	FIG 7		FIG		
9	Located next to the located at the top plastic cable suppo	center of grille.			
10	to remove. Caref cushioned surface	DEM Factory Grille should now be free and ready move. Carefully place the grille on a soft oned surface and prepare to remove the shutter onent which is currently fastened to the backside factory grille.			
11	Remove the (7) 10r outside edge and th center structure.			FIG 10	
12	Remove the (4) pla	stic clips located o	on the top lip.		
13	Set factory grille aside and prepare to install your new Grille.				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06LFC10G	Application	2015-2016 Ford F-150 Main Upper
14	Set all extension I	prackets in place	down on a flat cushioned surface. starting with large bracket on the lower bottom corners and the smal asten them with 10mm nuts.
15	Reinstall shutter co	mponent to new (Grille with factory hardware that was preciously removed.
16	Flip up and stand component to new		nit up to access top. Re-insert plastic clips which will than secure shutte
17		the grille was rem	stall on vehicle. Match it up to factory mounting points and reinstall in the noved. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts
18	Plug the (2) sensor component sensor		k into the shutter
	Place plastic radiat making sure the co		

to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06LFC10G	Application	2015-2016 Fo	ord F-150 Main Upper		
20	Carefully put back into place the headlight plastic body panel around the head lamp area making sure to alig with 8 tab fasteners and then firmly press into place. Use the (2) bolts to mount and secure the panel on the inside wheel well lip. on each side of the grille at the top corners, reinsert the plastic tabs. (1) on each side					
21	Reinstall the plastic shroud with the fasteners removed in Step 2.			N/A		
22	Installation completed!!!			N/A		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.