

Grille Installation Instruction

Part#	GR06L	FC10I	Applicat	tion	2015-2016	Ford H	-150 Main Upper		
	Item	Part	Name	QTY	Description	ltem	Part Name	QTY	Description
Parts Lis	1	Mesh Grille		1		4	Fender Washers	7	
Parts LIS	st2	2 "Z" Brackets (Long)		2		5	Nylon Lock Nuts	12	10-24
	3	"Z" Bracke	ets (Short)	3					
Install N	otes: O\	verlay ×	Rep	lacem	ent 🗸 🛛	Drill ×	Cut ×		
Step		Des	cription				illustration		
1	Identify the grille & hardware with parts list.								
2	Turn off engine and chalk tires with stop block . Open Hood.								
3	Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.								
4	Remove plastic shroud and then set aside for reinstallation later.								
	FIG 1	beide of the	a inner whe			Zmm belt	The headlight plastic box	ty nane	should pow
On the inside of the inner wheel well lip, remove (2) 7mm bolts. The headlight plastic body loose. You will need to coax panel out and off catch tabs to remove completely. The plastic should help.									
5		FIG 4		CALL OF THE OWNER		FIG		1	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Grille Installation Instruction

Part#	GR06LFC10I	Application	2015-2016 F	ord F-150 Main Upper		
6	On each side of the factory grille near the bottom corner just outside and behind, there is (1) 8mm bolt, (1) 8mm bolt on each side. Use 8mm socket to remove the (2) bolts.					
7	On top of the core	support, remove (4	4) 8mm bolts.			
8	Remove (4) plastic	clips on upper co	rner near head lam	ıp.		
	FIG 7		FIG			
9	Located next to the located at the top plastic cable suppo	center of grille.				
10	The OEM Factory to remove. Care cushioned surface component which i of the factory grille.	fully place the and prepare to re s currently fastene	grille on a soft emove the shutter	TO STORE OF		
11	Remove the (7) 10 outside edge and t center structure.			FIG 10		
12	Remove the (4) pla	astic clips located o	on the top lip.			
13	Set factory grille as Grille.	side and prepare to	o install your new	FIG 12		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06LFC10I	Application	2015-2016 Ford F-150 Main Upper			
14	With the new Grille unit placed face down on a flat cushioned surface. Set all extension brackets in place starting with large bracket on the lower bottom corners and the small brackets in the middle. Secure and fasten them with 10mm nuts.					
15	Reinstall shutter co	emponent to new (Grille with factory hardware that was preciously removed.			
16	Flip up and stand the entire grille unit up to access top. Re-insert plastic clips which will than secure shutter component to new Grille.					
17	Grille assembly is now ready to reinstall on vehicle. Match it up to factory mounting points and reinstall in the reverse order that the grille was removed. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts located near the bottom corners.					
18	Plug the (2) sensor component sensor		k into the shutter			
19	Place plastic radiat making sure the co of the shroud. Aligr the (10) plastic clip	Id air intake lip is on the factory mount	overlapped on top hting holes and use			

to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06LFC10I	Application	2015-2016 Fo	ord F-150 Main Upper
20	Carefully put back into place the headlight plastic body with 8 tab fasteners and then firmly press into place. Us inside wheel well lip. on each side of the grille at the top corners, reinsert the			e the (2) bolts to mount and secure the panel on the
21	Reinstall the plastic shroud with the fasteners removed in Step 2.			N/A
22	Installation completed!!!			N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.