

Grille Installation Instruction

Part#	GR06LFC10K Application		2015-2016 Ford F-150 Main Upper						
	Item	Part	Name	QTY	Description	ltem	Part Name	QTY	Description
Parts Lis	1	Mesh Grille		1		4	Fender Washers	7	
	2	"Z" Brackets (Long)		2		5	Nylon Lock Nuts	12	10-24
	3	3 "Z" Brackets (Short)		3					
Install N	otes: Ov	verlay ×	Rep	lacem	ent 🗸 🛛	Drill ×	Cut ×		
Step	Description					illustration			
1	Identify the grille & hardware with parts list.								
2	Turn off engine and chalk tires with stop block . Open Hood.								
3	Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.								
4	Remove plastic shroud and then set aside for reinstallation later.								
	FIG 1			FIG					
	On the inside of the inner wheel well lip, remove (2) 7mm bolts. The headlight plastic body panel should now loose. You will need to coax panel out and off catch tabs to remove completely. The plastic wedge spatula should help.								
5	FIG 4								

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Grille Installation Instruction

Part#	GR06LFC10K	Application	2015-2016 Fe	ord F-150 Main Upper			
6	On each side of the factory grille near the bottom corner just outside and behind, there is (1) 8mm bolt, (1) 8mm bolt on each side. Use 8mm socket to remove the (2) bolts.						
7	On top of the core support, remove (4) 8mm bolts.						
8	Remove (4) plastic clips on upper corner near head lamp.						
	FIG 7		FIG				
9	Located next to the located at the top plastic cable suppo	center of grille.					
10	The OEM Factory Grille should now be free and ready to remove. Carefully place the grille on a soft cushioned surface and prepare to remove the shutter component which is currently fastened to the backside of the factory grille.						
11	Remove the (7) 10mm plastic bolts that line the outside edge and the (1) 8mm bolt that is secures the center structure.						
12	Remove the (4) pla	stic clips located	on the top lip.				
13	Set factory grille aside and prepare to install your new Grille.						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



	GR06LFC10K	Application	2015-2016 Ford F-150 Main Upper			
14	With the new Grille unit placed face down on a flat cushioned surface. Set all extension brackets in place starting with large bracket on the lower bottom corners and the small brackets in the middle. Secure and fasten them with 10mm nuts.					
15	Reinstall shutter co	mponent to new (Grille with factory hardware that was preciously removed.			
16	Flip up and stand the entire grille unit up to access top. Re-insert plastic clips which will than secure shutter component to new Grille.					
17	Grille assembly is now ready to reinstall on vehicle. Match it up to factory mounting points and reinstall in the reverse order that the grille was removed. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts located near the bottom corners.					
18	Plug the (2) sensor component sensor		c into the shutter			

to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Part#	GR06LFC10K	Application	2015-2016 Fo	ord F-150 Main Upper	
20	Carefully put back into place the headlight plastic body panel around the head lamp area making sure to alig with 8 tab fasteners and then firmly press into place. Use the (2) bolts to mount and secure the panel on the inside wheel well lip. on each side of the grille at the top corners, reinsert the plastic tabs. (1) on each side				
21	Reinstall the plastic shroud with the fasteners removed in Step 2.			N/A	
22	Installation completed!!!			N/A	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.