

Grille Installation Instruction

Part#	GR07	GR07DEG78S		Application		For 2007-2013 GMC Yukon Not For Hybrid							
	Ite	n	Part N	lame QT		Description		ltem	Part Name		QTY	Description	
Parts Li	1	G	Grille		1	Stainless steel		4	'J' Hooks		6		
	2	В	Bolts		6	8 -32×2″		5	Wrench		1		
	3	K	K-Lock Nuts		6	8-32							
Install Notes: Overlay \checkmark Replacement \times Drill \times Cut \times													
Step	Description						illustration						
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and re-attach after installation.												
3	Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.												
4	Place one bolt through each of the holes on the grille. From the rear, place a 'J' hook on each bolt. Now thread a nut on each bolt. Then use the wrench to thread a bolt on the grille. $\label{eq:linear} \begin{split} & \end{tabular}$												
5	Make s	Make sure the insert is centered and tighten the hardware.											
6	Reinsta	Reinstall the black plastic cover which was removed in step 2.											
7	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!