AUTO PARTS SPECI	

## Grille Installation Instruction

Part#	G	R07D	FD74S	Applic	ation	For 2007-2013 GMC Sierra 1500 /2007-2010 GMC Sier Denali New Body With Logo Show							
		Item Part N		lame	QTY	Description		Item	P	Part Name		Description	
Parts L	ict	1 Grille			1	Stainless steel		4	'J'	Hooks	5		
Faits L	151	2 Bolts			10	8 -32×2	/	5	Tabs		5		
		3	3 K-Lock Nuts		10	8-32		6	Wren	nch	1		
Install Notes: Overlay $\checkmark$ Replacement $\times$ Drill $\times$ Cut $\times$													
Step	Description						illustration						
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and re-attach after installation.												
3	Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.												
4	Place one bolt through each of the holes on the grille. From the rear, place a 'J' hook (or a tab) on each bolt. Now thread a nut on each bolt. Then use the wrench to thread a bolt on the grille.												
5	Make sure the insert is centered and tighten the hardware.												
6	Reinstall the black plastic cover which was removed in step 2.												
7	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!